

1	2	3	4	5	6
REV.	REMARK	DATE	SIGN.		

SAS4x PLUG(P0) (HOST)		SATA CABLE RECEPTACLE (TARGET) (DEVICE PLUG PIN ASSIGNMENT)			
PIN	SIGNAL	REC.	PIN	SIGNAL	
S1	RX0+	P4	6	TX0+	
S2	RX0-		5	TX0-	
S15	TX0-		3	RX0-	
S16	TX0+		2	RX0+	
G1-G9		SIGNAL GROUND			
G1-G9		SIGNAL GROUND			
S3	RX1+	P3	6	TX1+	
S4	RX1-		5	TX1-	
S13	TX1-		3	RX1-	
S14	TX1+		2	RX1+	
G1-G9		SIGNAL GROUND			
G1-G9		SIGNAL GROUND			
S5	RX2+	P2	6	TX2+	
S6	RX2-		5	TX2-	
S11	TX2-		3	RX2-	
S12	TX2+		2	RX2+	
G1-G9		SIGNAL GROUND			
G1-G9		SIGNAL GROUND			
S7	RX3+	P1	6	TX3+	
S8	RX3-		5	TX3-	
S9	TX3-		3	RX3-	
S10	TX3+		2	RX3+	
G1-G9		SIGNAL GROUND			
G1-G9		SIGNAL GROUND			

DESC. SAS 4x PLUG TO SATA CABLE REC.4 CABLE ASSEMBLY					
P/N C3247-AMT Wiring CUSTOMER P/N					
APPROVED CHECKED DESIGNED TOLERANCE SCALE 1 = 1 UNIT mm					
DATE 12/04/06 DMC-MC DWG No. 2172					

DataStorageCables.com					
1	2	3	4	5	6