

1	2	3	4	5	6	7	8	9
REV.	REMARK	DATE	SIGN.					

WIRING DIAGRAM					
Mini SAS 4x			SAS 4x		
plug	PIN	SIGNAL	plug	PIN	SIGNAL
P1	A2	RX0+	P2	S16	TX0+
	A3	RX0-		S15	TX0-
	A5	RX1+		S14	TX1+
	A6	RX1-		S13	TX1-
	A8	RX2+		S12	TX2+
	A9	RX2-		S11	TX2-
	A11	RX3+		S10	TX3+
	A12	RX3-		S9	TX3-
	B2	TX0+		S1	RX0+
	B3	TX0-		S2	RX0-
	B5	TX1+		S3	RX1+
	B6	TX1-		S4	RX1-
B8	TX2+	S5	RX2+		
B9	TX2-	S6	RX2-		
B11	TX3+	S7	RX3+		
B12	TX3-	S8	RX3-		
GND GROUP			GND GROUP		
A1,A4,A7,A10,A13			G1-G9		
B1,B4,B7,B10,B13					

DataStorageCables.com	DESC.	Mini SAS 4x to SAS 4x cable assembly	APPROVED	CHECKED	DESIGNED	TOLERANCE	SCALE	1 = 1	UNIT	mm	
	P/N	C5256-xML-EQ	CUSTOMER P/N				DATE		DWG No:	DWG/B/1509	