


REV.	1	REMARK	2	DATE	3	SIGN.
------	---	--------	---	------	---	-------

ROHS



MATERIAL ROHS COMPLIANT:
 1. CABLE:
 CONDUCTOR: 24AWG SOLID SILVER PLATED COPPER.
 INSULATION: FOAM POLYOLEFIN.
 PAIR: 2 SINGLES LAID FLAT AND PARALLEL.
 CORE: 8 PAIRS
 PAIR DRAIN WIRE: 27AWG SOLID TINNED COPPER.
 PAIR SHIELD: ALUMINUM/POLYESTER TAPE. ALUMINUM SIDE FACING IN, 25% OVERLAP.
 INNER SHIELD: ALUMINUM/POLYESTER TAPE, ALUMINUM SIDE FACING OUT, 25% OVERLAP.
 OUTER SHIELD: 36AWG TIN PLATED COPPER BRAID, 85% COVERAGE.
 DIAMETER: 9.78MM NOMINAL
 PRINT LEGEND: "SPECTRA-STRIP SKEWCLEAR 8 PAIR 24 AWG (UL) 75C CL2 7MM 1/11 A 75C 300V FT4 LEAD FREE"
 DIFFERENTIAL IMPEDANCE: 100±5 OHMS @TDR

2. CONNECTOR:
 P1: Mini SAS 4x CABLE PLUG - 26CKT CONNECTOR (SFF-8088)
 (1) P.C.B: 4 LAYERS, GOLD PLATING ON CONTACT PADS.
 (2) LATCH: STAINLESS STEEL
 (3) BACKSHELL - ZINC DIE CASTING HOOD/ NICKEL PLATING
 (4) WITH EXTERNAL UNIVERSAL KEY
 P2: Mini SAS HD 4x CABLE PLUG (SFF-8644)
 (1) P.C.B: 6 LAYERS, GOLD PLATING ON CONTACT PADS.
 (2) LATCH: REVISED-STAINLESS STEEL.
 (3) BACKSHELL - ZINC DIE CASTING HOOD/ NICKEL PLATING
 (4) PULL TAB: NYLON UL94V-0, COLOR: BLUE.
 (5) EMI GASKET.
 3. FOR SAS 6.0 Gbps.
 4. TWO-WIRED SERIAL MEMORY: ATMEL AT24C02B EEPROM (256 BYTES).

DataStorageCables.com

DESC.	Mini SAS 4x/Mini SAS HD 4x CABLE ASS'Y	APPROVED	CHECKED	DESIGNED	TOLERANCE	SCALE	*	UNIT	mm	DWG NO:	DWG RC
P/N	C5556-10M			Sino		DATE	08/11/12				4779

1 2 3 4 5 6 7 8 9

