

1	2	3	4	5	6	7	8	9
REV.	REMARK	DATE	SIGN.					

WIRING DIAGRAM

Mini SAS 4x			Mini SAS 4i		
plug	PIN	SIGNAL	plug	PIN	SIGNAL
P1	A2	RX0+	P2	B2	TX0+
	A3	RX0-		B3	TX0-
	A5	RX1+		B5	TX1+
	A6	RX1-		B6	TX1-
	A8	RX2+		B13	TX2+
	A9	RX2-		B14	TX2-
	A11	RX3+		B16	TX3+
	A12	RX3-		B17	TX3-
	B2	TX0+		A2	RX0+
B3	TX0-	A3	RX0-		
B5	TX1+	A5	RX1+		
B6	TX1-	A6	RX1-		
B8	TX2+	A13	RX2+		
B9	TX2-	A14	RX2-		
B11	TX3+	A16	RX3+		
B12	TX3-	A17	RX3-		
GND GROUP			GND GROUP		
A1,A4,A7,A10,A13 B1,B4,B7,B10,B13			A1,A4,A7,A12,A15,A18 B1,B4,B7,B12,B15,B18		

DESC.	Mini SAS 4x to Mini SAS 4i cable assembly	APPROVED	CHECKED	DESIGNED	TOLERANCE	SCALE	1 = 1	UNIT	mm	
P/N	C5636-2M			KU		DATE	12/04/06	NO.	DWG/RC/2178	

DataStorageCables.com

1 2 3 4 5 6 7 8 9