

1		2		3		4		5		6			
REV.	REMARK			DATE	SIGN.								
<b>WIRING DIAGRAM(CONTROLLER TO BACKPLANE)</b>													
<b>SAS4X INTERNAL</b>						<b>SAS4X INTERNAL</b>							
REC.	PIN	SIGNAL				REC.	PIN	SIGNAL					
P1	32	GROUND				P2	1	GROUND					
	31	TX3+					2	RX3+					
	30	TX3-					3	RX3-					
	29	GROUND					4	GROUND					
	28	RX3-					5	TX3-					
	27	RX3+					6	TX3+					
	26	GROUND					7	GROUND					
	25	TX2+					8	RX2+					
	24	TX2-					9	RX2-					
	23	GROUND					10	GROUND					
	22	RX2-					11	TX2-					
	21	RX2+					12	TX2+					
	20	GROUND					13	GROUND					
	19	SIDE BAND 5					14	SIDE BAND 5					
	18	SIDE BAND 4					15	SIDE BAND 4					
	17	SIDE BAND 3					16	SIDE BAND 3					
	16	SIDE BAND 2					17	SIDE BAND 2					
	15	SIDE BAND 1					18	SIDE BAND 1					
	14	SIDE BAND 0					19	SIDE BAND 0					
	13	GROUND					20	GROUND					
12	TX1+				21	RX1+							
11	TX1-				22	RX1-							
10	GROUND				23	GROUND							
9	RX1-				24	TX1-							
8	RX1+				25	TX1+							
7	GROUND				26	GROUND							
6	TX0+				27	RX0+							
5	TX0-				28	RX0-							
4	GROUND				29	GROUND							
3	RX0-				30	TX0-							
2	RX0+				31	TX0+							
1	GROUND				32	GROUND							
<b>DataStorageCables.com</b>				DESC. SAS 4X TO SAS 4X INTERNAL CABLE ASSEMBLY									
				P/N I3232-.5M				CUSTOMER P/N					
				APPROVED	CHECKED	DESIGNED	TOLERANCE	SCALE	1 = 1	UNIT	mm		
						PPP		DATE	05/10/05	DWG NO:	DWC\B\929		