

	1	2	3	4	5	6	7	8	9	
REV.	REMARK	DATE	SIGN.							
F										F
E										E
D										D
C										C
B										B
A										A

WIRING DIAGRAM										
Mini SAS HD 4i (HOST)(P0)		SAS DRIVE CABLE REC.(TARGET)			4P POWER PLUG					
PIN	SIGNAL	rec.	PIN	SIGNAL	plug	PIN	SIGNAL			
B4	RX0+	P1	S6	TP+	P5	1	+12V			
B5	RX0-		S5	TP-			2	GND		
D5	TX0-		S3	RP-			4	+5V		
D4	TX0+		S2	RP+			3	GND		
GND GROUP			S1,S4,S7	GND						
		P13,P14,P15	+12V							
		P10,P11,P12	GND							
		P7,P8,P9	+5V							
		P4,P5,P6	GND							
A4	RX1+	P2	S6	TP+	P6	1	+12V			
A5	RX1-		S5	TP-			2	GND		
C5	TX1-		S3	RP-			4	+5V		
C4	TX1+		S2	RP+			3	GND		
GND GROUP			S1,S4,S7	GND						
		P13,P14,P15	+12V							
		P10,P11,P12	GND							
		P7,P8,P9	+5V							
		P4,P5,P6	GND							
B7	RX2+	P3	S6	TP+	P7	1	+12V			
B8	RX2-		S5	TP-			2	GND		
D8	TX2-		S3	RP-			4	+5V		
D7	TX2+		S2	RP+			3	GND		
GND GROUP			S1,S4,S7	GND						
		P13,P14,P15	+12V							
		P10,P11,P12	GND							
		P7,P8,P9	+5V							
		P4,P5,P6	GND							
A7	RX3+	P4	S6	TP+	P8	1	+12V			
A8	RX3-		S5	TP-			2	GND		
C8	TX3-		S3	RP-			4	+5V		
C7	TX3+		S2	RP+			3	GND		
GND GROUP			S1,S4,S7	GND						
		P13,P14,P15	+12V							
		P10,P11,P12	GND							
		P7,P8,P9	+5V							
		P4,P5,P6	GND							

GND GROUP:
A3,A6,A9,B3,B6,B9,
C3,C6,C9,D3,D6,D9.

DATA STORAGE CABLES	DESC.	Mini SAS HD 4i TO 4*SAS drive cable rec. with power cable ass'y			APPROVED	CHECKED	DESIGNED	TOLERANCE	SCALE	*	UNIT	mm	
	P/N	13529-1M	CUSTOMER P/N						DATE	01/21/'13	DWG NO:	DWG\RC\5965	