

	1	2	3	4	5	6	7	8	9
	REV.	REMARK	DATE	SIGN.					
F									F
E									E
D									D
C									C
B									B
A									A

  

WIRING DIAGRAM					
Mini SAS HD 4i(HOST)			SATA internal cable rec.(TARGET)		
PLUG	PIN	SIGNAL	REC.	PIN	SIGNAL
P0	B4	RX0+	P1	6	TX+
	B5	RX0-		5	TX-
	D5	TX0-		3	RX-
	D4	TX0+		2	RX+
	GND GROUP			1,4,7	GROUND
A4	A4	RX1+	P2	6	TX+
	A5	RX1-		5	TX-
	C5	TX1-		3	RX-
	C4	TX1+		2	RX+
	GND GROUP			1,4,7	GROUND
B7	B7	RX2+	P3	6	TX+
	B8	RX2-		5	TX-
	D8	TX2-		3	RX-
	D7	TX2+		2	RX+
	GND GROUP			1,4,7	GROUND
A7	A7	RX3+	P4	6	TX+
	A8	RX3-		5	TX-
	C8	TX3-		3	RX-
	C7	TX3+		2	RX+
	GND GROUP			1,4,7	GROUND

GND GROUP:  
A3,A6,A9,B3,B6,B9,  
C3,C6,C9,D3,D6,D9.

DATA STORAGE CABLES	DESC.	Mini SAS HD 4i to 4* SATA internal cable rec. cable ass'y			APPROVED	CHECKED	DESIGNED	TOLERANCE	SCALE	*	UNIT	mm	
	P/N	I3547-0.5M	CUSTOMER P/N						DATE	01/21/'13	DWG NO:	DWG\RC\5971	